DESCRIPTION

5   CONSTANT VELOCITY UNIVERSAL JOINT

TECHNICAL FIELD

       The present invention relates to a constant velocity

universal joint which can be used as, for example, a shaft

10   coupling for steering of an automobile.

BACKGROUND ART

       In a steering shaft for an automobile, for example, a

plurality of Cardan joints (cross shaft couplings) was

15   generally used. The Cardan joint is a not-constant

velocity universal joint in which the larger an operating

angle, the larger the rotational fluctuation between an

input axis and an output axis becomes. Ensuring constant

velocity by combining a plurality of Cardan joints causes a

20   problem that flexibility in vehicle design is impaired.

       Using a fixed-type constant velocity universal joint

as a shaft coupling for steering has the advantage that the

flexibility in vehicle design increases because constant

velocity is ensured at any operating angle.

25   Fig. 9 shows a fixed-type constant velocity universal

joint (Rzeppa-type constant velocity universal joint: ball fixed joint) which is conventionally used as a coupling joint of a drive shaft and the like in an automobile. The constant velocity universal joint comprises: an outer member 11 in which six curved track grooves 11b are formed in a spherical inside diameter surface 11a thereof in an axial direction; an inner joint member 12 in which six curved track grooves 12b are formed in a spherical outside diameter surface 12a in the axial direction, and an engagement section 12c having teeth (serrations or splines) are formed in an inside diameter surface thereof; six torque transmission balls 13 which are disposed in respective six ball tracks, which are formed by the synergy between the track grooves 11b of the outer member 11 and the track grooves 12b of the inner joint member 12 corresponding to the track grooves 11b; and a retainer 14 which has pockets 14c for holding the torque transmission balls 13.

The center A of the track groove 11b of the outer member 11 with respect to the spherical center of the inside diameter surface 11a and the center B of the track groove 12b of the inner joint member 12 with respect to the spherical center of the outside diameter surface 12a are offset oppositely to each other (the center A is offset on the side of an opening of the joint, and the center B is

2

offset on the side of a deeper side of the joint in an example shown in the drawing) at the same distance in the axial direction. Thus, the ball track, which is formed by the synergy between the track groove 11b and the track

5 groove 12b corresponding thereto, is in the shape of a wedge opening to one of the axial directions (on the side of the opening of the joint in the example shown in the drawing). Both of the spherical center of the inside diameter surface 11a of the outer member 11 and the

10 spherical center of the outside diameter surface 12a of the inner joint member 12 are in a joint center plane O including the center of the torque transmission ball 13.

Even if the outer member 11 is displaced from the inner joint member 12 at an angle θ, the torque

15 transmission balls 13 guided by the retainer 14 are always maintained in a bisector plane ($\theta/2$) of the angle θ at any operating angle θ, and hence the constant velocity of the joint is ensured.

In this kind of fixed-type constant velocity universal

20 joint, by the way, there are clearances between the track groove of the outer member and the ball and between the track groove of the inner member and the ball by the reasons of function and processing. This track clearance appears when one of the inner member and the outer member

25 is fixed in a neutral state of the joint, and the other one

3

is moved in the axial direction or is rotated in a circumferential direction.

The track clearance has large effect on the wobbliness (rotation backlash) between the inner member and the outer member in the circumferential direction. Since the track clearance is indispensable in the fixed-type constant velocity universal joint for the reasons of processing tolerance and assembly, the rotational backlash becomes large. Accordingly, it is ~~concerned~~ a concern that using the joint as a steering joint for the automobile as-is may cause deterioration in steering operability in the vicinity of straight-ahead driving of a vehicle and the occurrence of unusual noise.

As a mean ~~means~~ to solve this problem, a fixed-type constant velocity universal joint is proposed in which preload means provided inside the joint fills an axial clearance caused by the track clearance in order to restrain the rotational backlash (refer to, for example, Patent Document 1).

In the constant velocity universal joint having such preload means, which always ~~making~~ make the balls contact ~~to~~ the ball tracks to restrain the rotational backlash, inside the joint, a first object of the present invention is to further miniaturize the joint and ensure ~~the~~ ~~enough~~ sufficient strength, load-carrying capacity, and

4

durability in order to provide ~~the~~ a constant velocity universal joint especially suitable for a steering shaft of an automobile.

Next, a second object of the present invention will be described. Fig. 10 shows the retainer 14 of the constant velocity universal joint described above. The retainer 14 has six window-shaped pockets 14c for holding the torque transmission balls 13 in circumferentially equidistant positions. Both circumferential sides of the pocket 14c are pillar sections 14d. Generally, the pockets 14c of the retainer 14 were cut by a press, and then a pair of axial walls 14c1 {refer to Fig. 10(b)} opposed in the axial direction was subjected to finishing processing by shaving (broach). In this case, the axial initial clearance between the pocket 14c and the torque transmission ball 13 is set at -50 μm to -10 μm by processing the axial walls 14c1. If there are variations in a processing margin of the axial wall 14c1, however, the center positions of the pockets 14c are misaligned among the pockets 14c arranged in the circumferential direction, so that the so-called pocket staggered state occurs and the strength and durability of the retainer 14 become worse. Therefore, a radius of curvature R in corner round sections 14c3 of the pocket 14c is made small, and straight sections 14c4 are left. The axial dimension δ between the axial wall 14c1

and the straight section 14c4 is controlled to prevent the occurrence of the so-called pocket staggered state. Accordingly, making the radius of curvature R of the corner round section 14c3 small results in the extension of a pocket area to an originally functionally unnecessary part.

Accordingly, since the pocket area is too large for its function, the pillar sections of the retainer are under high stress. The surface areas of an inside diameter surface and an outside diameter surface become small, so that there is a concern that ~~the enough~~sufficient strength and durability of the retainer cannot be ensured.

In the constant velocity universal joint having preload means for always making the balls contact ~~to~~ the ball tracks, a second object of the present invention is to optimize pocket structure without impairing the function of the retainer in order to increase the strength and durability of the retainer, and by extension the strength and durability of the joint.

Patent Document 1: Japanese Patent Laid-Open Publication No. 2003-130082

DISCLOSURE OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

To solve the foregoing first object, a constant velocity universal joint according to a first invention of

6

this application comprises: an outer member which is provided with a spherical inner surface in which a plurality of track grooves are formed; an inner member which is provided with a spherical outer surface in which a plurality of track grooves are formed, balls disposed in a wedge-shaped ball track which is formed by the synergy between the track groove of the outer member and the track groove of the inner member; a retainer disposed between the spherical inner surface of the outer member and the spherical outer surface of the inner member to hold the balls; a press section which is provided in the inner member and applies elastic pressure in an axial direction; and a receiver section which is provided in the retainer and receives the pressure from the press section. The constant velocity universal joint is characterized in that a ratio $r1$ (= PCD_{BALL}/D_{BALL}) of a pitch circle diameter (PCD_{BALL}) of the ball to a diameter (D_{BALL}) of the ball is in a range of $1.5 \leqq r1 \leqq 4.0$.

The pitch circle diameter (PCD_{BALL}) of the ball is twice ($PCD_{BALL} = 2 \times PCR$) as long as the length of a segment connecting the center of the track groove of the outer joint member or the center of the track groove of the inner member and the center of the ball {the length of a segment connecting the center of the track groove of the outer joint member and the center of the ball is equal to

7

the length of a segment connecting the center of the track groove of the inner member and the center of the ball. Thus, constant velocity of the joint is ensured. This length will be hereinafter called (PCR)}.

The reason of $1.5 \leqq r1 \leqq 4.0$ is that it is difficult for the constant velocity universal joint to extensively vary the PCD of the ball within the confines of limited space, and the value of $r1$ mainly depends on the diameter of the ball. Since the constant velocity universal joint for steering is used within the confines of low load torque in comparison with a conventional constant velocity universal joint, the inner and outer member can be thinner. In case of $r1 < 1.5$, however, the thickness of the outer member, the inner member, or the like becomes too thin, so that there is a concern about a lack of strength. In case of $4.0 < r1$, the load-carrying capacity of the ball and each track surface becomes small, so that there is a concern about durability.

In other words, it is difficult for the constant velocity universal joint to extensively vary the pitch circle diameter (PCD_{BALL}) of the ball within the confines of limited space. Thus, the value of $r1$ mainly depends on the diameter (D_{BALL}) of the ball. In case of $r1 < 1.5$ (generally when the diameter D_{BALL} of the ball is large), the thickness of another member (the outer member, the

8

inner member, or the like) becomes too thin, so that there is concern about lack of strength. Contrarily in case of r1 > 4.0 (generally when the diameter D_{BALL} is small), the load-carrying capacity becomes small, so that there is

5 concern about durability. $1.5 \leqq r1 \leqq 4.0$ makes it possible to sufficiently ensure the strength of the outer member and the like and the load-carrying capacity and durability of the joint. This is corroborated by tests.

10 Table 1

r1	1. 1	1. 5	1. 9	2. 3	2. 7	3. 1	3. 5	3. 9
durability	○	○	○	○	○	○	○	○
strength of outer ring	×	△	△	○	○	○	○	○
strength of inner ring	×	△	△	○	○	○	○	○
strength of retainer	×	△	△	○	○	○	○	○

○ : good △ : fair × : no good   (six balls)

As shown in Table 1 (Table 1 shows evaluations based

15 on comparative tests), in the case of r1 = 1.1, the strength of the outer member, the inner member, and the retainer is not sufficiently ensured, and undesirable results are obtained. In the cases of r1 = 1.5 and 1.9, tolerable results are obtained in respect of strength.

9

Especially in case of r1 ≧ 2.3, the strength of the inner member, the outer member, and the retainer and the durability of the joint are sufficiently ensured, and desirable results are obtained. The tests are not carried out in a range of r1 > 3.9, but it is assumed that desirable results are obtained as with above. In case of r1 > 4.0, however, durability seems to be a problem, so that r1 ≦ 4.0 is desirable.

As described above, r1 should be set in a range of 1.5 ≦ r1 ≦ 4.0, and more preferably in a range of 2.3 ≦ r1 ≦ 4.0.

The reason why r1 is set in a range of 1.5 to 4.0 times is because the strength of an inner ring 2 is reduced when r1 is less than 1.5 times. When r1 is more than 4.0 times, on the other hand, there occurs the inconvenience that the strength of the retainer 4 is reduced and also the outside diameter of the outer joint member becomes large.

According to a second invention of this application, in addition to the foregoing structure, a ratio $r2$ (= D_{OUTER}/ PCD_{SERR}) of an outside diameter (D_{OUTER}) of the outer joint member to a pitch circle diameter (PCD_{SERR}) of teeth of coupling serrations formed in the inside diameter surface of the inner member is in a range of 3.0 ≦ r2 ≦ 5.0.

The reason of 3.0 ≦ r2 ≦ 5.0 is as follows. The

10

pitch circle diameter (PCD_{SERR}) of the teeth of the inner member cannot be extensively varied in relation to the strength of the other axis and the like. Thus, the value of r2 mainly depends on the outside diameter (D_{OUTER}) of the outer joint member. In case of r2 < 3.0 (generally when the outside diameter D_{OUTER} is small), the thickness of each member (the outer member, the inner member, or the like) becomes too thin, so that there is a concern about strength. In the case of r2 > 5.0 (generally when the outside diameter D_{OUTER} is large), on the other hand, a practical problem may occur due to its dimensions and the like, and the object of miniaturization cannot be achieved. $3.0 \leqq r2 \leqq 5.0$ can ensure the strength of the outer member and the like and the durability of the joint, and also satisfy a practical request.

As described above, it is desirable that r2 is set in a range of $3.0 \leqq r2 \leqq 5.0$.

According to a third invention of this application, the center of the track groove of the outer joint member with respect to a spherical center of an inside diameter surface and the center of the track groove of the inner member with respect to the spherical center of an outside diameter surface are offset oppositely to each other at the same distance (F) in an axial direction. A ratio R1 (= F/PCR) between the foregoing offset amount (F) and the

11

foregoing (PCR) is in a range of $0.109 \leqq R1 \leqq 0.162$.

The reason of $0.109 \leqq R1 \leqq 0.162$ is as follows. Assuming that PCR is fixed, a track load (a load applied to a contact section between the track groove and the ball) is generally reduced with increase in the offset amount (F) in giving an operating angle. Therefore, the large offset amount (F) has an advantage in respect of the track load.

However, if the offset amount (F) is too large,: (1) a track becomes shallow in a large operating angle region, and hence allowable load torque is reduced; (2) a movement amount of the ball in the direction of the diameter increases in the pocket of the retainer, so that it becomes necessary to increase the thickness (dimension in the direction of the diameter) of the retainer in order to prevent the ball from dropping off. Thus, the track becomes shallow, and the allowable load torque is reduced; (3) a movement amount of the ball in a circumferential direction increases in the pocket of the retainer, so that it becomes necessary to extend the circumferential dimension of the pocket of the retainer in order to ensure the proper movement of the ball. Thus, pillar sections of the retainer become narrow, and there is a problem of strength.

If the offset amount (F) is too small, on the other hand: (4) peak values of a track load (P1) on a loaded side

12

and a track load (P2: a phase for applying a load to a track on an unloaded side occurs during a single rotation) on an unloaded side increase (P1 and P2 indicate the peak values at predetermined phase angles), and hence durability is reduced; and (5) a maximum operating angle is reduced.

As described above, the offset amount (F) is desirable neither too large nor too small, an optimum range exists by striking a balance between the foregoing problems (1) to (3) and the foregoing problems (4) and (5). Since the optimum range of the offset amount (F) varies with the size of the joint, it is necessary to get the optimum range in relation to fundamental dimensions representing the size of the joint. Accordingly, this is the reason why the ratio R1 (= F/PCR) between the track offset F and the dimension of PCR is used. The foregoing (1) to (3) matter in R1 > 0.162, and the foregoing (4) and (5) matter in R1 < 0.109. The optimum range of the offset amount (F) is $0.109 \leqq R1 \leqq 0.162$ in terms of ensuring the allowable load torque, ensuring the strength of the retainer, reduction in the track load, ensuring durability, and ensuring the maximum operating angle.

A fourth invention of the present application is characterized in that the number of the torque transmission balls is equal to or less than six, and a contact angle (θ) between the track and the ball is in a range of $30^{\circ} \leqq$

13

$\theta \leqq 40°$.

The constant velocity universal joint for steering is
always used at a large operating angle, in contrast to that
for a drive shaft. In the specifications of the
conventional universal joint for the drive shaft which is
used around a contact angle of 45°, ~~45° ,~~ a contact ellipse
between the track groove and the ball runs onto a track
edge under a heavy load, and the allowable load torque of
inner and outer ring tracks at a large angle region becomes
short, so that there is a concern about durability. As a
measure for solving this problem, to prevent the contact
ellipse from running onto the track edge under the heavy
load even in the large angle area, setting the contact
angle (θ) at the range of $30° \leqq \theta \leqq 40°$ can achieve
improvement in an allowable load torque diagram.

Fifth to seventh inventions of the present application
are combinations of the foregoing first invention and
eighth to tenth inventions of the present application
described below.

To solve the foregoing second object, a constant
velocity universal joint according to the eighth invention
of this application comprises: an outer member which is
provided with a spherical inner surface in which a
plurality of track grooves are formed; an inner member
which is provided with a spherical outer surface in which a

14

plurality of track grooves are formed; balls disposed in a wedge-shaped ball track which is formed by the synergy between the track groove of the outer member and the track groove of the inner member; and a retainer disposed between

5   the spherical inner surface of the outer member and the spherical outer surface of the inner joint member to hold the balls. The ball always makes contact with the ball track by preload applying means. In such a constant velocity universal joint, the ball track is open to one of

10   the axial directions in the shape of a wedge. A pocket of the retainer has corner round sections, and a ratio (R/d) between a radius of curvature R of the corner round section and a diameter d of the torque transmission ball is R/d $\geqq$ 0.22.

15   The reason why the ratio (R/d) is in the foregoing range is as follows. Fig. 7 shows the results of FEM analysis indicating the relationship between the ratio (R/d) and a maximum principal stress load applied to a pillar section (an interval section between the pockets

20   adjoining in a circumferential direction). From the results shown in the drawing, it was recognized that a diagram of {(R/d) - (maximum principal stress load)} took a minimum value at R/d = 0.537. It was confirmed that the maximum principal stress load of the pillar section was

25   theoretically minimized at R/d = 0.537.

15

As shown in Table 2, on the basis of the analysis results, an R dimension satisfying R/d = 0.537 was obtained at each size of the torque transmission ball.

Furthermore, since the general tolerance (general tolerance: when classification of standard dimensions exceeds 6 mm, allowable tolerance is ± 1 mm) of the R dimension is ± 1 mm, the maximum value and the minimum value of the R dimension were obtained, and then the maximum value and the minimum value of R/d corresponding to each value were obtained (the typical value of R/d was an average value of the maximum value and the minimum value). As a result, 0.45 ≦ R/d ≦ 0.62 was obtained as the desirable range of R/d. On the other hand, a conventional retainer shown in Fig. 10 satisfies R/d = 0.21, and the reduction effect of the maximum principal stress load can be expected at R/d ≧ 0.22.

Therefore, the ratio (R/d) was set in a range of R/d ≧ 0.22, and more preferably in a range of 0.45 ≦ R/d ≦ 0.62. Setting the ratio (R/d) in the foregoing range makes it possible to minimize pocket space without impairing the function (operability ~~to~~ of the torque transmission balls) of the retainer, and hence it is possible to increase the surface areas of an inside diameter surface and an outside diameter surface of the retainer. Accordingly, it is possible to increase the strength and durability of the

16

retainer in cooperation with the reduction effect of the
maximum principal stress load in the pillar section.

Table 2

ball diameter (d)	R dimension			R/d		
	O. 537d	maximum value	minimum value	upper limit	medium	lower limit
12. 7	6. 8	7. 8	5. 8	0. 614	0. 535	0. 457
14. 287	7. 7	8. 7	6. 7	0. 609	0. 539	0. 469
15. 081	8. 1	9. 1	7. 1	0. 603	0. 537	0. 471
15. 875	8. 5	9. 5	7. 5	0. 598	0. 535	0. 472
16. 669	9	10	8	0. 6	0. 54	0. 48
17. 462	9. 4	10. 4	8. 4	0. 596	0. 538	0. 481
18	9. 7	10. 7	8. 7	0.594	0. 539	0. 483
19. 05	10. 2	11. 2	9. 2	0. 588	0. 535	0. 483
19.844	10.7	11.7	9.7	0. 59	0.539	0.489
20. 638	11. 1	12. 1	10. 1	0. 586	0. 538	0. 489
general torerance : -±1 (exceedsR6)				0. 58 ~ 0. 614	0.535 ~ 0. 54	0. 457~ 0. 496

The ninth invention of the present application
provides a structure in which the pocket of the retainer
has corner round sections, and the ratio (R/d) between the
radius of curvature R of the corner round section and the
diameter d of the torque transmission ball is R/d ≧ 0.22,
and more preferably 0.45 ≦ R/d ≦ 0.62. This invention
may be applied to a constant velocity universal joint with
a straight section which has a straight fillet in each

17

track groove of the outer member and the inner joint
member. The other matters are the same as those in the
constant velocity universal joint of the invention
described above.

5   In the constant velocity universal joint according to
the present invention, the torque transmission balls are
integrated as follows. Relatively varying the angle
between the outer member and the inner member, in such a
state that the pocket of the retainer faces to the outside
10   from an opening section of the outer member on one side,
the torque transmission ball is integrated into the pocket
of the retainer and the ball track. When the angle between
the outer member and the inner member relatively varies,
the torque transmission balls held in the pockets of the
15   retainer relatively move in the circumferential direction.
Thus, it is necessary to set the circumferential length of
the pockets of the retainer in such a manner that the
already integrated torque transmission ball relatively
moving in the circumferential direction does not interfere
20   with circumferential walls of the pocket of the retainer
during integrating the torque transmission balls (the
displacement angle between the outer member and the inner
member at this time is called "ball integration angle").

       Since the six pockets of the retainer can be composed
25   of one kind of pocket, the circumferential lengths thereof

18

are the same. Setting the ratio (R/d) at a value in the
foregoing range, as described above, can improve the
strength and durability of the retainer, so that it is also
possible to equalize the circumferential lengths of all six
pockets (the same length as the foregoing second pocket) as
in the tenth invention of this application.

Of the walls of the pocket of the retainer, it is
preferable that at least a pair of axial walls opposed in
an axial direction of the retainer are formed by cutting
after heat treatment of the retainer. "Cutting" here
includes grinding, cutting by quenched steel, and the like.
Accordingly, since variations in a processing margin of the
axial wall are reduced, it is possible to eliminate a
straight section, which is provided in conventional pocket
structure to control the processing margin of the axial
wall. Thus, it is possible to increase the radius of
curvature of the corner round section, and hence set the
ratio (R/d) at a value in the foregoing range.

ADVANTAGE OF THE INVENTION

According to the first invention, it is possible to
further miniaturize the size of the constant velocity
universal joint and to sufficiently ensure strength, load-
carrying capacity, durability, and an operating angle in
the constant velocity universal joint which has preload

19

means inside the joint for always making the balls contact ~~to~~ the ball tracks to restrain rotational backlash.

According to the eighth invention, the structure of the pocket can be optimized without impairing the function of the retainer, so that it is possible to increase the strength and durability of the retainer, and by extension the strength and durability of the joint.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a longitudinal sectional view of a constant velocity universal joint for steering to which the present invention is applied;

Fig. 2 is a cross sectional view of the joint of Fig. 1;

Fig. 3 is a sectional view of a plunger unit section;

Fig. 4 is an enlarged sectional view of the plunger unit section;

Fig. 5(a) is a cross sectional view of a retainer;

Fig. 5(b) is a longitudinal sectional view of a retainer;

Fig. 6 is an enlarged plan view showing the periphery of a pocket of the retainer;

Fig. 7 is a graph showing the relationship between a ratio (R/d) and a maximum principal stress load of a pillar section;

20

Fig. 8(a) is a plan view of a steering device;

Fig. 8(b) is a side view of the steering device;

Fig. 8(c) is a perspective view of the steering device;

5   Fig. 9(a) is a longitudinal sectional view showing a conventional constant velocity universal joint;

Fig. 9(b)} is a cross sectional view showing a conventional constant velocity universal joint;

Fig. 10(a) is a longitudinal sectional view of a

10   conventional retainer; and

Fig. 10(b) is an enlarged plan view showing the periphery of a pocket in the conventional joint.

BEST MODE FOR CARRYING OUT THE INVENTION

15   An embodiment of the present invention will be hereinafter explained with reference to drawings.

The embodiment of a constant velocity universal joint according to the present invention will be described in detail. The embodiment described below takes a case where

20   the present invention is applied to a Rzeppa-type (BJ), being a kind of fixed-type constant velocity universal joint, as an example. The present invention, however, is not limited to that, and is also applicable to an undercut free joint (UJ). A constant velocity universal joint

25   according to the present invention is available for not

21

only steering but also a drive shaft and a propeller shaft.

First, a steering device in which the fixed-type constant velocity universal joint is installed will be explained in brief. The steering device, as shown in Figs. 8(a) to (c), transmits the rotational motion of a steering wheel 66 to a steering gear 68 through a steering column being composed of one or a plurality of steering shafts 62 for the purpose of converting the rotational motion into the reciprocating motion of a tie rod 69. In the case where the steering shafts 62 cannot be disposed in a straight line due to mounting space or the like, one or a plurality of shaft couplings is disposed between the steering shafts 62 so as to be able to transmit correct rotational motion to the steering gear 68 even in a state of bending the steering shafts 62. In the embodiment of the present invention, the fixed-type constant velocity universal joint is used as the shaft coupling 61. A symbol α in Fig. 8(b) represents a bend angle of the joint, and a large bend angle exceeding $30°$ can be set. The steering device may be an electric power steering device (EPS) in which a motor applies auxiliary power, or may be a hydraulic power steering device.

A fixed-type constant velocity universal joint A for steering according to the embodiment of the present invention, as shown in Fig. 1, has a connecting shaft 5

22

with a yoke 70 connected to a steering shaft. The fixed-
type constant velocity universal joint A~is configured to
include: an outer member 1 being an outer joint member in
which six curved track grooves 1a are formed in a spherical
inside diameter surface 1b in an axial direction; an inner
joint member 2 in which six curved track grooves 2a are
formed in a spherical outside diameter surface 2b in the
axial direction, and an engagement section 2d having teeth
(serrations or splines) for coupling the connecting shaft 5
are formed in an inside diameter surface; six torque
transmission balls 3 disposed in six ball tracks which are
formed by the synergy between the track grooves 1a of the
outer member 1 and the track grooves 2a of the inner joint
member 2 corresponding to the track grooves 1a; and a
retainer 4 which holds the torque transmission balls 3.

An axial end section of the connecting shaft 5 engages
with the engagement section 2d of the inner joint member 2
with teeth (serration engagement or spline engagement).
The inner joint member 2 and the connecting shaft 5 compose
an inner member 6.

A rubber or resin boot 20 is attached between the
outer member 1 and the connecting shaft 5 to prevent the
entry of dust and the like into the joint.

In this embodiment, the center O_1 of the track groove
1a of the outer member 1 with respect to the spherical

23

center of the inside diameter surface 1b and the center O_2 of the track groove 2a of the inner joint member 2 with respect to the spherical center of the outside diameter surface 2b are offset oppositely to each other (the center O_1 is on the side of an opening of the joint, and the center O_2 is on a deeper side of the joint in an example shown in the drawing) at the same distance (F) in the axial direction. Thus, the ball track, which is formed by the synergy between the track groove 1a and the track groove 2a corresponding thereto, is in the shape of a wedge opening to one of the axial directions (on the side of the opening of the joint in the example shown in the drawing). Both of the spherical center of an outside diameter surface 4b of the retainer 4 and the spherical center of the inside diameter surface 1b of the outer member 1 being a guide surface of the outside diameter surface 4b of the retainer 4 are in a joint center plane O including the center O_3 of the ball 3. Also, both of the spherical center of an inside diameter surface 4c of the retainer 4 and the spherical center of the outside diameter surface 2b of the inner joint member 2 being a guide surface of the inside diameter surface 4c of the retainer 4 are in the joint center plane O. Accordingly, the foregoing offset amount (F) of the outer member 1 is the axial distance between the center O_1 of the track groove 1a and the joint center plane

24

O. The foregoing offset amount (F) of the inner joint member 2 is the axial distance between the center O_2 of the track groove 2a and the joint center plane O, and hence both offset amounts are equal. The center O_1 of the track groove 1a of the outer member 1 and the center O_2 of the track groove 2a of the inner joint member deviate oppositely (the center O_1 of the track groove 1a is on the side of the opening of the joint, and the center O_2 of the track groove 2a is on the deeper side of the joint) at the same distance (F) with respect to the joint center plane O in the axial direction. Each of the length of a segment connecting the center O_1 of the track groove 1a of the outer member 1 and the center O_3 of the ball 3 and the length of a segment connecting the center O_2 of the track groove 2a of the inner member 2 and the center O_3 of the ball 3 is PCR. Both lengths are equal.

When the outer member 1 is displaced from the inner joint member 2 at an angle θ, the balls 3 guided by the retainer 4 are always maintained in a bisector plane ($\theta/2$) of the angle θ at any operating angle θ, and hence the constant velocity of the fixed-type constant velocity universal joint A̶ is ensured.

In the fixed-type constant velocity universal joint A̶, as shown in Figs. 1, 3, and 4, a plunger unit 50 is attached to an axial end of the connecting shaft 5

25

connected to the steering shaft through the yoke 70 in
order to restrain rotational backlash. The plunger unit 50
is an assembly which comprises a ball 53 being a press
member having a press section 52 in its end, a compression
coil spring 54 being an elastic member, and a case 55 being
a container member for containing the ball 53 and the
compression coil spring 54. The compression coil spring 54
is a source of elastic force which presses the ball 53 on
the deeper side of the outer member 1 (in a ball protruding
direction).

The structure of attaching the foregoing plunger unit
50 to the connecting shaft 5 is as follows. In this
embodiment, a press section 52 is formed in the connecting
shaft 5, and a receiving section 58 is formed in the
retainer 4. The receiving section 58, however, may be
provided in the connecting shaft 5 and the press section 52
may be provided in the retainer 4 contrarily, as long as
the inner member 6 and the retainer 4 are relatively
pressed.

The plunger unit 50, as shown in Fig. 3, is fixed when
its case 55 is press-fitted or bonded to a recessed section
5a formed in the axial end of the connecting shaft 5. When
the case 55 is completely fixed, a flange 55b of the case
55 engages with an axial end surface of the connecting
shaft 5, so that the position of the plunger unit 50 is

26

fixed with reference to the axial end surface. In other
words, it is possible to fix the position of the plunger
unit 50 if there are variations in the depth of the
recessed section 5a of the connecting shaft 5 due to its
5   processing tolerance, because the depth of the recessed
section 5a is larger than the axial length of the case 55
of the plunger unit 50 and the flange 55b engages with the
axial end surface of the connecting shaft 5.

The case 55 of the plunger unit 50 is in the shape of
10   a cylinder with a bottom, and an engaged section 55a
protruding on the side of an inside diameter is provided at
the edge of its opening end. Since the inside diameter ϕd
of the engaged section 55a is smaller than the outside
diameter ϕD of the ball 53, it is possible to prevent the
15   ball 53 from dropping off. Accordingly, the ball 53, the
compression coil spring 54, and the case 55 are assembled
into a unit. As to means for providing an engaged section
to prevent the ball 53 from dropping off, various
structures are available in addition to forming the engaged
20   section 55a by swaging the edge of the opening end of the
case 55 along the whole circumference.

As shown in Figs. 3 and 4, a receiver member 56 is
attached to an end section of the retainer 4 on the deeper
side of the outer member 1. The receiver member 56 is in
25   the shape of a lid covering an opening at an end of the

retainer 4, and is composed of a spherical section 56a in a partial spherical shape and an attachment section 56b formed in the outer periphery of the spherical section 56a in the shape of a ring. The inner surface (surface opposed to the connecting shaft 5) of the spherical section 56a is a concave spherical surface which functions as the receiving section 58 for receiving pressure from the press section 52. The attachment section 56b is fixed in the end of the retainer 4 by proper means such as press or welding.

To smoothly slide the press section 52 of the plunger unit 50 on the receiving section 58 of the receiver member 56 when the connecting shaft 5 of the constant velocity universal joint takes an operating angle, as shown in Fig. 4, the inside diameter Ro of the receiving section 58 in a recessed spherical shape is set larger than the outside diameter (ϕD/2) (refer to Fig. 3) of the ball 53 having the press section 52 (Ro > (ϕD/2)). To prevent the interference between the receiver member 56 and the inner joint member 2 in taking an operating angle θ, the radius Ro of the inside diameter of the receiving section 58 is set larger than the radius Ri of the spherical inner surface of the retainer 4 (Ro > Ri).

In the foregoing structure, when a serration shaft section of the connecting shaft 5 and the inner joint member 2 are coupled by serrations and attaching a snap

28

ring 59 completely couples both (refer to Figs. 3 and 4),
the press section 52 of the plunger unit 50 and the
receiving section 58 of the receiver member 56 come into
contact with each other, and then the ball 53 is retracted

5   and the compression coil spring 54 is compressed. Since
the position of the plunger unit 50 is fixed with respect
to the axial end surface of ~~the~~ a connecting shaft 5, as
described above, it is possible to always keep the contact
state between the press section 52 and the receiving

10   section 58 by stabilizing the attachment state of the press
section 52, and hence pressure from the press section 52
can securely act on the receiving section 58.

In this embodiment, in addition to structure described
above, the primary diameters of the joint are set as

15   follows. As described above, (I) it is preferable that the
ratio r1 (= PCD_{BALL}/D_{BALL}) between the pitch circle diameter
PCD_{BALL} ($PCD_{BALL} = 2 \times PCR$) of the ball 3 and the diameter
D_{BALL} thereof is set in a range of $1.5 \leqq r1 \leqq 4.0$, and more
preferably in a range of $2.3 \leqq r1 \leqq 4.0$ for the purpose

20   of ensuring the strength of the outer member and the like,
ensuring load-carrying capacity, and ensuring durability.
(II) The ratio r2 (= D_{OUTER}/PCD_{SERR}) between the outside
diameter D_{OUTER} of the outer member 1 and the pitch circle
diameter PCD_{SERR} of the serrations (or splines) 2d of the

25   inner joint member 2 is set in a range of $3.0 \leqq r2 \leqq 5.0$.

29

The structure of the above (I) may be adopted alone.

The offset amount (F) of the track grooves 1a and 2a may be set as follows. As described above, (III) it is preferable that the offset amount (F) of the track grooves 1a and 2a is set so that the ratio R1 (= F/PCR) between a track offset F and PCR is in a range of 0.109 ≦ R1 ≦ 0.162 for the purpose of ensuring allowable load torque, ensuring the strength of the retainer, reduction in a track load, ensuring durability, and ensuring a maximum operating angle.

Fig. 5 shows the retainer 4. The retainer 4 is provided with six window-shaped pockets 4a for containing and holding the torque transmission balls 3 and pillar sections 4d between the pockets 4a adjoining in the circumferential direction. In this embodiment, the circumferential lengths of each pocket 4a are all equal. The difference (= L - d) between the axial dimension L of the pocket 4a and the diameter d of the torque transmission ball 3 at the start of operation of the joint, that is, the axial initial clearance between them is controlled in a range of 0 to + 50 μm, and more preferably in a range of 0 to + 30 μm. The retainer 4 is made of, for example, carburized steel which has a carburized layer in its surface due to carburizing and quenching. Chrome steel, chromium molybdenum steel, nickel chrome molybdenum steel,

or the like is available as the carburized steel.

As shown in Fig. 6 in enlargement, the pocket 4a of the retainer 4 comprises a pair of axial walls 4a1 opposed in the axial direction of the retainer 4, a pair of circumferential walls 4a2 opposed in the circumferential direction, and corner round sections 4a3 connecting the axial wall 4a1 and the circumferential wall 4a2. In this embodiment, the ratio (R/d) of the radius of curvature R of the corner round section 4a3 to the diameter d of the torque transmission ball 3 is set in a range of $0.45 \leqq R/d \leqq 0.62$. Also, the circumferential wall 4a2 and the corner round sections 4a3 are drawn in a single arc with the radius of curvature R. Furthermore, as to the axial walls 4a1, grinding, cutting by quenched steel, or the like is carried out after the heat treatment (carburizing and quenching) of the retainer 4 in order to reduce variations in a processing margin (the circumferential walls 4a2 and the corner round sections 4a3 are remained as-is after a cutting process by press).

31